


Diamond Design Mat

Product Specifications

| DIAMOND DESIGN MAT | | | | | | | | |
|----------------------------|-----------|------------------|--------------------------------------------------------------------------------------|------------------|---------------------|---------------|-----------------------|-------------|
| Code | Thickness | Specific Gravity | Hardness | Tensile Strength | Elongation On Break | Tear Strength | Application | Polymer |
| | MM | Gm/cm3 | SHORE A | Kg/cm2(min) | % | Kg/cm2 | | |
| DDGP 70150 | 3 | 1.5 | 70+/-5 | 70 | 250 | 22 | General Purpose | NR/SBR |
| DDOR 70140 | 3 | 1.4 | 70+/-5 | 85 | 300 | 45 | Oil Resistant | NITRILE |
| DDHT 60125 | 4 | 1.25 | 60+/-5 | 125 | 350 | 25 | High Traffic areas | NR/SBR |
| DDOU 65130 | 3 | 1.3 | 65+/-5 | 80 | 250 | 25 | Outdoor use | EPDM |
| DDEI-N 70155 | 6.5 | 1.55 | 70+/-5 | 50 | 250 | 20 | Electrical Insulation | NR/SBR |
| DDEI-E 75150 | 3.5 | 1.5 | 75+/-5 | 60 | 250 | 30 | Electrical Insulation | NR/SBR |
| DDFR 70155 | 3 | 1.55 | 70+/-5 | 50 | 250 | 20 | Fire Resistant | CHLOROPRENE |
| STANDARD DIMENSIONS | | | COLORS | | | | | |
| MAXIMUM WIDTH: 1.2 M | | |  | | | | | |
| LENGTH: 10 M, 15 M, 20 M | | | | | | | | |