

**Tolerances:
Sheet Rubber & Diaphragm Sheet**

as published in Rubber Manufacturers Association, Sheet Rubber Handbook, dated 1980

Thickness Tolerances*				
Nominal Thickness			Tolerances (Plus or Minus)	
Fractions Inches	Decimals Inches	Millimeters	Inches	Millimeters
Under 1/32"	Under 0.031	Under 0.79	0.01	0.25
1/32" to but not including 1/16"	0.031 to 0.062	0.79 to 1.59	0.012	0.3
1/16" to but not including 1/8"	0.062 to 0.125	1.59 to 3.18	0.016	0.4
1/8" to but not including 3/16"	0.125 to 0.187	3.18 to 4.8	0.02	0.51
3/16" to but not including 3/8"	0.187 to 0.375	4.8 to 9.5	0.031	0.79
3/8" to but not including 9/16"	0.375 to 0.562	9.5 to 14.3	0.047	1.19
9/16" to but not including 3/4"	0.562 to 0.750	14.3 to 19.2	0.062	1.59
3/4" to but not including 1"	0.750 to 1.000	19.2 to 25.4	0.094	2.38
1" and over	1.000 and over	25.4	10%	10%
Note - Material made by the coating process is subject to considerably more restrictive tolerances:				
under 0.031" (0.79 mm), ± 0.003" (± 0.08 mm); 0.031" (0.79 mm) and over, ± 10%				
Width Tolerances*				
Widths available in 36" and 48" with a 5% tolerance				
Length Tolerances*				
Lengths available from 25ft to 150ft with a 2% tolerance				

Terms and conditions of sale are subject to change without notice