

**Tolerances:
Sheet Rubber & Diaphragm Sheet**

as published in Rubber Manufacturers Association, Sheet Rubber Handbook, dated 1980

| Thickness Tolerances* | | | | |
|---|-----------------|--------------|---------------------------------------|-------------|
| Nominal Thickness | | | Tolerances (Plus or Minus) | |
| Fractions Inches | Decimals Inches | Millimeters | Inches | Millimeters |
| Under 1/32" | Under 0.031 | Under 0.79 | 0.01 | 0.25 |
| 1/32" to but not including 1/16" | 0.031 to 0.062 | 0.79 to 1.59 | 0.012 | 0.3 |
| 1/16" to but not including 1/8" | 0.062 to 0.125 | 1.59 to 3.18 | 0.016 | 0.4 |
| 1/8" to but not including 3/16" | 0.125 to 0.187 | 3.18 to 4.8 | 0.02 | 0.51 |
| 3/16" to but not including 3/8" | 0.187 to 0.375 | 4.8 to 9.5 | 0.031 | 0.79 |
| 3/8" to but not including 9/16" | 0.375 to 0.562 | 9.5 to 14.3 | 0.047 | 1.19 |
| 9/16" to but not including 3/4" | 0.562 to 0.750 | 14.3 to 19.2 | 0.062 | 1.59 |
| 3/4" to but not including 1" | 0.750 to 1.000 | 19.2 to 25.4 | 0.094 | 2.38 |
| 1" and over | 1.000 and over | 25.4 | 10% | 10% |
| Note - Material made by the coating process is subject to considerably more restrictive tolerances: under 0.031" (0.79 mm), ± 0.003" (± 0.08 mm); 0.031" (0.79 mm) and over, ± 10% | | | | |
| Width Tolerances* | | | | |
| Widths available in 36" and 48" with a 5% tolerance | | | | |
| Length Tolerances* | | | | |
| Lengths available from 25ft to 150ft with a 2% tolerance | | | | |

Terms and conditions of sale are subject to change without notice